



TECHNICAL SPECIFICATION TIKKA T3 BATTUE

WEAPON	TIKKA T3
MODEL	BATTUE
MANUFACTURER	SAKO Ltd., FINLAND
AVAILABLE ACTION SIZES	Right hand / STD Left Hand / -
OPERATION	Tikka T3 manually operated bolt action
BOLT	2 locking lugs, plunger ejection
CALIBER / RATE OF TWIST / MAGAZINE CAPACITY	308 Win / 11" / (3 in magazine, 1 in chamber) 338 Federal / 10" / (3 in magazine, 1 in chamber) 7x64 / 10" / (3 in magazine, 1 in chamber) 30-06 Sprg / 11" / (3 in magazine, 1 in chamber) 8x57IS / 9.5" / (3 in magazine, 1 in chamber) 9.3x62 / 14" / (3 in magazine, 1 in chamber) 300 Win Mag / 11" / (3 in magazine, 1 in chamber) 300 Win Short Mag / 11" / (3 in magazine, 1 in chamber)
OVERALL WEIGHT w/o ACCESSORIES	T3 / 3.1 kg (6 13/16 lbs)
OVERALL LENGTH	T3 / 1020 mm (40 3/16")
BARREL LENGTH	T3 / 510 mm (20")
LENGTH OF PULL	Minimum 335mm (13.2") adjustable with spacers
BARREL	Fluted light hunting contour barrel (cold hammer forged)
MAGAZINE	Detachable single row synthetic magazine (T3 short magazine)
SIGHTS	Special open sights with adjustable rear sight (elevation) Battue sights are provided with illuminated dots
OPTICAL SIGHT ATTACHMENT	17mm dovetail rail
METAL PARTS SURFACE FINISHING	Blued metal parts
STOCK	Matte oiled walnut stock
TRIGGER MECHANISM	Single stage trigger, adjustable pull 1 to 2kg (2 to 4 lbs) (Optional set trigger)
SAFETY	Two stage safety
ACCESSORIES	Manual

