



TECHNICAL SPECIFICATION TIKKA T3 SPORTER

WEAPON	TIKKA T3
MODEL	SPORTER
MANUFACTURER	SAKO Ltd., FINLAND
AVAILABLE ACTION SIZES	Right hand / STD Left Hand / available
OPERATION	Tikka T3 manually operated bolt action
BOLT	2 locking lugs, plunger ejection
CALIBER / RATE OF TWIST / MAGAZINE CAPACITY	222 Rem / 14" / (6 in magazine, 1 in chamber) 223 Rem / 8", 12" / (6 in magazine, 1 in chamber) 6.5x55 SE / 8" / (5 in magazine, 1 in chamber) 260 Rem / 8" / (5 in magazine, 1 in chamber) 308 Win / 11" / (5 in magazine, 1 in chamber)
OVERALL WEIGHT w/o ACCESSORIES	510 mm (20") Barrel 4.1 kg (9.0 lbs) 600 mm (24") Barrel 4.4 kg (9.7 lbs)
OVERALL LENGTH	1050 mm (41.3") with 510 mm (20") barrel 1140 mm (44.9") with 600 mm (24") Barrel
BARREL LENGTH	510 mm (20") Muzzle thread included 600 mm (24") Optional Muzzle thread
LENGTH OF PULL	Minimum 335mm (13.2") adjustable with spacers
BARREL	Heavy contour barrel (cold hammer forged)
MAGAZINE	Detachable single row synthetic magazine (T3 long magazine)
SIGHTS	No open sights
OPTICAL SIGHT ATTACHMENT	17mm dovetail rail and threads for picatinny mount
METAL PARTS SURFACE FINISHING	Blued metal parts
STOCK	Laminate stock, orange grey
SWIVEL STUDS	Forend equipped with rail sling swivel and basic rear stock swivel
TRIGGER MECHANISM	Single stage trigger, adjustable pull 1 to 2kg (2 to 4 lbs) (optional set trigger)
SAFETY	Two stage safety
ACCESSORIES	Manual

